




## KALU

floor stand, double-headed, LED, 3000K, white/black, 24°

The puristic design of the KALU FLOOR 2 floor stand is the guarantee of completely free direction of the lamp head. The integrated COB LED module provides an even lighting effect. Delivery includes a connection lead and a foot switch for direct connection to 230V mains supply.



## TECHNICAL DATA

|                                     |                          |
|-------------------------------------|--------------------------|
| Item no.:                           | 1000126                  |
| Lamps included                      | 0                        |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V   |
| Secondary power / secondary voltage | 700 mA/V                 |
| Vertical tilting range              | 120 °                    |
| Horizontal rotation range           | 340 °                    |
| Length                              | 28.0 cm                  |
| Width                               | 9.9 cm                   |
| Height                              | 16.3 cm                  |
| Net weight                          | 1.826 kg                 |
| Gross weight                        | 2.143 kg                 |
| IP Code                             | IP 20                    |
| Safety class                        | I                        |
| Impact resistance class             | IK03                     |
| Impact resistance                   | 0,3499999999999998 Joule |
| Assembly                            | Mobile                   |
| Dimmable                            | Ja                       |
| Dimming technology                  | trailing edge            |
| Wattage                             | 31.0 W                   |
| Lumen                               | 2000 lm                  |
| Colour temperature                  | 3000 Kelvin              |
| Beam angle                          | 24 °                     |



|              |         |
|--------------|---------|
| Color        | white   |
| CRI          | >80     |
| Binning      | 6       |
| LXXBXX data  | 70/50   |
| Service life | 40000 h |

**Notes**

---

---

---

---

---