



## ANINDA

wall and recessed ceiling light, LED, 3000K, short, silver-grey, 90°

The rectangular ANINDA is a professional recessed ceiling and wall light which has been specially manufactured for hollow ceilings and walls. The light outlet is covered by acrylic glass. A suitable constant current driver providing 700mA is required to operate the recessed luminaire.



## TECHNICAL DATA

Item no.:	1000388
Lamps included	0
Secondary power / secondary voltage	700 mA/V
Length	60.5 cm
Width	5.8 cm
Height	8.6 cm
Installation length	59.0 cm
Installation width	4.5 cm
Installation depth	8.5 cm
Net weight	1.097 kg
Gross weight	1.443 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Wattage	16.0 W
Lumen	1040 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	grey
CRI	>80
Binning	3

## Accessories

1001133	LED driver , 700mA, 12.5-25W, dimmable
1001136	LED driver , 700mA, 12.6-19.6W
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable

## Notes

---

---

---

---

---