


## LYNAH

pendant, double-headed, LED, 3000K, black

With its timeless and modern design in black and white and its efficiency, the LYNAH luminaire series is an innovative lighting option for any area. The lamp holders are multi-directional, thus allowing the individual focus of the light beam. The luminaire is equipped with dimmable LED modules with a beam angle of 24° each, and is ready for direct connection to 230V power supply.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1000410                |
| Lamps included                      | 0                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 350 mA/V               |
| Vertical tilting range              | 180 °                  |
| Length                              | 45.0 cm                |
| Pendant length                      | 150.0 cm               |
| Width                               | 16.0 cm                |
| Height                              | 5.9 cm                 |
| Net weight                          | 2.543 kg               |
| Gross weight                        | 2.9 kg                 |
| IP Code                             | IP 20                  |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling                |
| Dimmable                            | Ja                     |
| Dimming technology                  | trailing edge          |
| Wattage                             | 28.0 W                 |
| Lumen                               | 1900 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 24 °                   |
| Color                               | black                  |



|              |         |
|--------------|---------|
| CRI          | >80     |
| Binning      | 6       |
| LXXBXX data  | 70/50   |
| Service life | 40000 h |

**Notes**

---

---

---

---

---