



## KARPO

wall and recessed ceiling light, LED, 3000K, 80°, black, incl. switch,

KARPO series lights are available in white and black. It has a spot in a cylindrical shape which can be individually aligned via the hinge on the flat canopy. The swivel and tilting range allows you to optimally light up the room. The integrated premium LEDs provide high energy efficiency. To operate, the single-headed FRAME Spots needs a suitable constant current driver rated at 500mA.

## TECHNICAL DATA

|                                     |               |
|-------------------------------------|---------------|
| Item no.:                           | 1000673       |
| Lamps included                      | 0             |
| Secondary power / secondary voltage | 500 mA/V      |
| Vertical tilting range              | 90 °          |
| Horizontal rotation range           | 330 °         |
| Length                              | 15.5 cm       |
| Height                              | 6.0 cm        |
| Diameter                            | 3.0 cm        |
| Installation length                 | 6.5 cm        |
| Installation width                  | 4.0 cm        |
| Installation depth                  | 2.0 cm        |
| Net weight                          | 0.189 kg      |
| Gross weight                        | 0.289 kg      |
| IP Code                             | IP 20         |
| Safety class                        | III           |
| Assembly                            | Recessed      |
| Assembly details                    | Ceiling, Wall |
| Wattage                             | 5.0 W         |
| Lumen                               | 360 lm        |
| Colour temperature                  | 3000 Kelvin   |
| Beam angle                          | 40 °          |
| Color                               | black         |



### Accessories

|        |  |
|--------|--|
| 464091 | LED DRIVER , 9VA, 500mA, incl. strain relief |
|--------|--|

|              |         |
|--------------|---------|
| CRI          | >90     |
| Binning      | 6       |
| LXXBXX data  | 70/50   |
| Service life | 30000 h |

### Notes

---

---

---

---

---