

## **APONI 120**

outdoor floor stand, LED, anthracite, 3000K, IP65

With the aluminium APONI 120 floor stand, the opalescent PC illumination surface is closed off with an aluminium cap. With protection class IP55, it is suitable for outdoor use. A connection box is optionally available for simplified installation. The luminaire, which comes in two sizes, is connected directly to the 230V mains power supply because of the dimmable LED constant current driver. The APONI series also includes wall lights and can therefore be used universally.

## **TECHNICAL DATA**

Item no.:	1000683
Primary nominal voltage	220-240V ~50/60Hz mA/V
Height	120.0 cm
Diameter	7.2 cm
Net weight	1.753 kg
Gross weight	2.539 kg
IP Code	IP 65
Safety class	I
Assembly	Surface
Assembly details	Ground
Wattage	8.0 W
Lumen	440 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	549

							4				4			4		4		4	ч	4	4	ч	4	4	4	ч	4									
	J.	- 4		а	J	J	J.	J,	J	J.	J	J	J	J	J	a,	ä	J.	J.																	
ı J	J	ר ר	ı	J	J	J	J	J.	J	1	J	J.	J	J	J	J	J		ä			J		J.		1	J.	ı	J.	J	J.	ı	ı	L	١,	١,
					ы					а		а	a.	а	a.	а	а	л	J.	a.	1	J.	J.	ı	1		а	ы								



## Accessories

228730	CONNECTION BOX , 3-pin, IP68
--------	------------------------------

Notes		