



DISOS

outdoor floodlight, LED, 3000K, black, 70W, IP65

Powerful DISOS LED floodlight to light up areas and courtyards. With a tiltable installation bracket and protection class Ip65, the floodlight is suitable for outdoor installation on the wall or on the floor. The electrical connection of the spotlight, which is available in warm-white, is made directly to the 230V mains power supply using the built-in driver and connection lead. Various wall brackets are available for easy wall mounting. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	1000805
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	100-240V ~50/60Hz mA/V
Secondary power / secondary voltage	900 mA/V
Length	25.5 cm
Width	12.0 cm
Height	30.0 cm
Net weight	3.757 kg
Gross weight	4.544 kg
IP Code	IP 65
Safety class	I
Impact resistance class	IK06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground,Wall
Wattage	71.0 W
Lumen	7200 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	black
CRI	>80

Accessories

228730	CONNECTION BOX , 3-pin, IP68
234340	Wall bracket , for Outdoor Beam and MILOX floodlight, black, 50cm
234345	WALL BRACKET for MILOX 1 and MILOX 2 , anthracite, 50 cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm
234355	WALL BRACKET for MILOX 1 and MILOX 2 , anthracite, 80 cm

Binning	6
LXXBXX data	70/50
Service life	35000 h

Notes
