



MEDO 30

recessed fitting, LED, 3000K, white, 1-10V

The high-quality MEDO 30 recessed ceiling light convinces with its clear form and the elegant material contrast of its aluminium and glass construction. The luminaire is available in black, white, and silver grey. The luminaire can be dimmed via a 1-10V interface. Its integrated Premium LED gives pleasant lighting effects, and its built-in LED driver allows direct connection to 230V mains supply.





TECHNICAL DATA

| Item no.: | 1000852 | |
|-------------------------------------|------------------------|--|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | |
| Secondary power / secondary voltage | 350 mA/V | |
| Height | 11.0 cm | |
| Diameter | 30.0 cm | |
| Installation diameter | 29.0 cm | |
| Installation depth | 15.0 cm | |
| Net weight | 1.622 kg | |
| Gross weight | 2.112 kg | |
| IP Code | IP 20 | |
| Safety class | 1 | |
| Assembly | Recessed | |
| Assembly details | Ceiling | |
| Wattage | 15.0 W | |
| Lumen | 1000 lm | |
| Colour temperature | 3000 Kelvin | |
| Beam angle | 105 ° | |
| Color | white | |
| CRI | >80 | |
| UGR ? | 25.0000 | |
| Binning | 6 | |
| LXXBXX data | 70/50 | |
| | | |





| Service life | 25000 h |
|--------------|---------|
| | |

| Notes | | |
|-------|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |