



REVILO

wall and ceiling light, LED, 3000K, black, 36°

The REVILO is available in white and black. It has a cylindrical spotlight which can be individually directed via a joint. The swivel and tilting range allows you to optimally light up the room. The integrated premium LEDs provide high energy efficiency. The built-in LED constant current driver allows it to be directly connected to a 230V mains power supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1000901 |
| Lamps included | 0 |
| Number of different light outlets | 1 |
| Primary nominal voltage | 100-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V |
| Vertical tilting range | 180 ° |
| Horizontal rotation range | 350 ° |
| Length | 11.5 cm |
| Height | 13.0 cm |
| Diameter | 5.0 cm |
| Net weight | 0.389 kg |
| Gross weight | 0.489 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Wall |
| Wattage | 9.5 W |
| Lumen | 670 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | black |
| CRI | >80 |



| | |
|---------------------|---------|
| Binning | 3 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
