

VALETO® DIMMER for RECESSED WALL INSTALLATION

for SLV VALETO® SMART HOME SYSTEM

You can adapt your lighting to your frame of mind at any time: You are in full control of the light temperature with the SLV VALETO® WALL-MOUNTED DIMMER. The control unit can be operated using the remote control (Remote Control CCT/DIM 420021) or via a Gateway (430001).

TECHNICAL DATA

Item no.:	1001008
Length	4.6 cm
Width	4.7 cm
Height	1.8 cm
Net weight	0.034 kg
Gross weight	0.039 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling, Wall
Dimmable	Ja
Dimming technology	trailing edge
Color	white
Minimum ambient temperature	0 °C
Maximum ambient temperature	40 °C
Color Minimum ambient temperature	white 0 °C

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	J J .	ר ר	ı	J	ı	J	J	J.	J	ä	J	J	J	J	J	J	J		4			ı		4		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					ă,			á		ä		J	ä	J	ä	J	J	J	J.	J	ă,	a.	J.	J	J	J	J.	ă,								


