



IMPERVA 150 CW

LED Outdoor wall and ceiling light, IP66, grey, 3000K

The functional wall and ceiling light has a diffuser which creates a pleasant light distribution. The luminaire was designed with powerful LEDs and is available in several lengths. The IP luminaire can be fitted with a warm white or cool white LEDs as required. Thanks to the built-in ballast, the luminaire is ready for direct connection to the 230V mains voltage supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1001316 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 1050 mA/V |
| Length | 156.0 cm |
| Width | 12.0 cm |
| Height | 10.8 cm |
| Net weight | 2.361 kg |
| Gross weight | 2.991 kg |
| IP Code | IP 66 |
| Safety class | I |
| Impact resistance class | IK08 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Number of through-wires | 30 |
| Wattage | 55.0 W |
| Lumen | 6600 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120 ° |
| Color | grey |
| CRI | >80 |
| Binning | 4 |



| | |
|-----------------------------|---------|
| LXXBXX data | 70/50 |
| Service life | 50000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 687 |

Notes
