




LED FLOOD LIGHT

80W, black, 5700K, 90°

Powerful FLOOD LIGHT spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An earth spike is available as an option for simplified floor installation.



TECHNICAL DATA

Item no.:	1001644
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1150 mA/V
Vertical tilting range	180 °
Length	31.8 cm
Width	10.5 cm
Height	40.8 cm
Net weight	4.828 kg
Gross weight	5.314 kg
IP Code	IP 65
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ground, Wall
Wattage	81.0 W
Lumen	7200 lm
Colour temperature	5700 Kelvin
Beam angle	90 °
Color	black
CRI	>80
Binning	5
LXXBXX data	70/50
Service life	30000 h

Maximum ambient temperature	40 °C
BIG WHITE Page	606

Accessories

228730	CONNECTION BOX , 3-pin, IP68
234340	Wall bracket , for Outdoor Beam and MILOX floodlight, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm

Notes
