




## NAPIA TWIN WL

LED Indoor surface-mounted wall light, white, 3000K

The NAPIA TWIN wall profile luminaire consists of an LED cornice that gives off atmospheric, indirect lighting. In addition, the NAPIA TWIN has two separately switchable LED spots which, thanks to their tilt range, can be adjusted to the desired position. With a 32° beam angle, the spots provide an ideal focussed reading light. Thanks to the pre-installed LED driver, the NAPIA TWIN is suitable for direct connection to the 230V mains supply.



## TECHNICAL DATA

Item no.:	1001822
Lamps included	0
Number of different light outlets	3
Primary nominal voltage	220-240V ~50/60Hz mA/V
Vertical tilting range	90 °
Horizontal rotation range	350 °
Width	200.0 cm
Height	13.0 cm
Depth	8.6 cm
Net weight	5.213 kg
Gross weight	5.957 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Wall
Wattage	21.0 W
Lumen	565 lm
Colour temperature	3000 Kelvin
Beam angle	32 °
Color	white
CRI	>80
Binning	6



Binning 2	6
LXXBXX data	70/50
Service life	35000 h
Service life 2	35000 h
BIG WHITE Page	200

**Notes**

---

---

---

---

---