



NEW TRIA angular

LED indoor recessed ceiling light, brushed aluminium, 1800-3000K 7.2W

The square, 240V version of our popular NEW TRIA LED recessed fitting series is available with white, black or brushed aluminium housings. The swivelling range of this recessed spotlight ensures that you can individually focus the light beam. The LEDs can be adjusted to the required light colour using the innovative Dim to Warm technology. Specifically designed for a hole diameter of 68 mm, the NEW TRIA 68 recessed fitting is supplied ready for direct connection to the 230V alternating current. The scope of delivery of the product includes clip and leaf springs for convenient adaptation to the respective fitting situation.

TECHNICAL DATA

Item no.:	1001993
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Vertical tilting range	30 °
Length	8.2 cm
Width	8.2 cm
Height	4.0 cm
Installation diameter	7.0 cm
Installation depth	4.0 cm
Net weight	0.237 kg
Gross weight	0.304 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Ja
Dimming technology	Dim-to-Warm
Wattage	7.2 W
Lumen	430 lm
Beam angle	38 °
Color	aluminium
CRI	>95



Binning	3
LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	491

Notes
