

HELIA 40 PD

LED indoor pendant, soft gold, 3000K, surface-mounted version

With the HELIA 40 you have a pendant with a purist and clear design. This luminaire is available in soft gold, black, white and brushed copper. A 9 W warm-white premium LED is integrated, this is supplied from the built-in constant current driver. The luminaire is delivered with a 1.5 m connection lead. This means the luminaire is ready for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	1002171
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Length	45.0 cm
Pendant length	150.0 cm
Diameter	4.0 cm
Net weight	0.867 kg
Gross weight	1.078 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Wattage	12.0 W
Lumen	720 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	gold
CRI	>90
Binning	6
LXXBXX data	70/50
Service life	30000 h
Maximum ambient temperature	30 °C

								4				4			-		-		-	-	4	-	-	-	4	4	4	4									
	- 4		ı		a,	4	a,	4	J	J.	a,	J	J	J	J	J	a,	a,	a,	J.																	
ı	T T	J.	1	ı	J	1	4	1	4	4	4	4	J	J	4	4	1	J		4			J		J.		1	J	J	J.	J.	ı	1	۱,	. د	1	1
						а			а		а		а	a.	а	J.	л	a.	J.	J.	J.	а	J.	a.	ı	ı	a.	а	а								



BIG WHITE Page	73
----------------	----

otes	