



DASAR® Flat

outdoor LED recessed floor light, stainless steel 304, 4000K, IP67, 4.3W

The 240V inground fitting DASAR FLAT 80 has a round stainless steel shade and frosted glass cover and is fitted with a high-performance power LED module. Because it is in protection class IP67, the luminaire - which is available with three light colours - is suitable for outdoor use. The electrical connection is made using the connection lead included directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly. This luminaire contains built-in LED lamps.

TECHNICAL DATA

| | |
|-------------------------|--------------------|
| Item no.: | 1002188 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50/60Hz mA/V |
| Height | 5.8 cm |
| Diameter | 8.0 cm |
| Installation diameter | 8.8 cm |
| Installation depth | 5.7 cm |
| Net weight | 0.425 kg |
| Gross weight | 0.491 kg |
| IP Code | IP 67 |
| Safety class | I |
| Impact resistance class | IK08 |
| Impact resistance | 5 Joule |
| Assembly | Recessed |
| Assembly details | Ground,Wall |
| Wattage | 4.3 W |
| Lumen | 110 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 125 ° |
| Color | stainless steel |
| CRI | >80 |
| Binning | 3 |

Accessories

| | |
|--------|------------------------------|
| 228730 | CONNECTION BOX , 3-pin, IP68 |
|--------|------------------------------|

| | |
|-----------------------------|---------|
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Mechanical loading | 0,18 t |
| BIG WHITE Page | 722 |

Notes
