




ALMINO WL

LED outdoor surface-mounted wall light, UGR<19, grey, IP65, 4000K

With the ALMINO luminaire family we are providing ceiling lights and wall lights which can be optionally suspended for professional use with the highest demands. Thanks to the robust casing and the built-in LEDs, the luminaires provide efficient basic lighting with limited direct glare (UGR<19) and are therefore particularly suitable for industrial areas, warehouses and logistics areas. A suspension set and mounting brackets are available as optional accessories.



TECHNICAL DATA

Item no.:	1002195
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	300 mA/V
Vertical tilting range	180 °
Length	20.6 cm
Width	25.2 cm
Height	9.8 cm
Net weight	1.241 kg
Gross weight	1.456 kg
IP Code	IP 65
Safety class	II
Impact resistance class	IK08
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	45.0 W
Lumen	6200 lm
Colour temperature	4000 Kelvin
Beam angle	50 °
Color	grey
CRI	>80
UGR ?	19.0000



Binning	3
LXXBXX data	70/50
Service life	50000 h
Minimum ambient temperature	-30 °C
Maximum ambient temperature	60 °C
BIG WHITE Page	190

Notes
