



LED SPIKE

LED outdoor ground spike luminaire, anthracite, IP55, 3000K, 40°

The LED SPIKE ground spike luminaire is available in several colour variants and comes equipped with a powerful, warm-white 6 Watt LED. The luminaire is made of aluminium and is connected using the supply cable incl. plug directly to the 230V mains supply. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use.

TECHNICAL DATA

| Item no.: | 1002201 | | | |
|-------------------------------------|------------------------|--|--|--|
| Primary nominal voltage | 100-240V ~50/60Hz mA/V | | | |
| Secondary power / secondary voltage | 240 mA/V | | | |
| Vertical tilting range | 360 ° | | | |
| Length | 8.0 cm | | | |
| Length of earth spike | 17.2 cm | | | |
| Height | 10.0 cm | | | |
| Diameter | 6.0 cm | | | |
| Net weight | 0.55 kg | | | |
| Gross weight | 0.617 kg | | | |
| IP Code | IP 55 | | | |
| Safety class | I | | | |
| Impact resistance class | IK06 | | | |
| Impact resistance | 1 Joule | | | |
| Assembly | Mobile | | | |
| Wattage | 6.0 W | | | |
| Lumen | 400 lm | | | |
| Colour temperature | 3000 Kelvin | | | |
| Beam angle | 40 ° | | | |
| Color | anthracite | | | |
| CRI | >80 | | | |
| Binning | 3 | | | |





| LXXBXX data | 80/50 |
|----------------|---------|
| Service life | 30000 h |
| BIG WHITE Page | 590 |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |