




DASAR® 270

Outdoor LED inground fitting, 3000K, round, IP67, asymmetrical beam

If you wish to use inground fittings in open spaces or to illuminate your pond, the IP 65 / IP 67 safety class is the important thing. The DASAR® 270 has the required safety class and is therefore protected from penetration by dust and water (even if occasionally submerged). The inground fitting is round and has asymmetric light distribution. A premium LED is installed in the DASAR® 270. This gives off particularly pleasant light in your outdoor area. We stand by our products. SLV has now been a powerful partner with regard to lighting for approximately 40 years, and gives a 5 year warranty.



TECHNICAL DATA

Item no.:	1002893
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Height	20.3 cm
Diameter	27.0 cm
Installation diameter	25.0 cm
Installation depth	19.9 cm
Net weight	5.3 kg
Gross weight	5.671 kg
IP Code	IP 65 / IP 67
Safety class	I
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Number of through-wires	60
Wattage	30.0 W
Lumen	2000 lm
Colour temperature	3000 Kelvin
Color	black
CRI	>80
Binning	3



LXXBXX data	70/50
Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Mechanical loading	2 t
BIG WHITE Page	733

Notes
