




NOTAPO I

Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO I WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO I recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	1002979
Secondary power / secondary voltage	700 mA/V
Width	3.6 cm
Height	10.5 cm
Depth	3.8 cm
Installation length	10.0 cm
Installation width	2.8 cm
Installation depth	5.0 cm
Net weight	0.077 kg
Gross weight	0.118 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall, Wall with Acc.
Wattage	2.2 W
Lumen	6 lm
Colour temperature	3000 Kelvin
Color	white
CRI	>90
Binning	6
LXXBXX data	70/50
Service life	35000 h

Maximum ambient temperature	40 °C
BIG WHITE Page	440

Accessories

1002981	NOTAPO I and II WL installation frame
464142	LED DRIVER , 10.5W, 700mA, incl. strain relief, dimmable
464200	LED DRIVER , 3W, 700mA, incl. strain relief

Notes
