



## **ABRIDOR SENSOR**

Outdoor LED surface-mounted wall light IP55 anthracite 3000/4000K

The aluminium luminaires in the ABRIDOR family provide solutions for the wall light and floor stand area. Thanks to its IP55 protection class, the luminaires are suitable for outdoor use. The electrical connection is made directly to the 230V mains power supply. The unusual lamp head means that the built-in LED has particularly wide light distribution.

## **TECHNICAL DATA**

Item no.:	1002990
Primary nominal voltage	100-277V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Length	14.0 cm
Height	16.0 cm
Depth	17.5 cm
Net weight	1.262 kg
Gross weight	1.557 kg
IP Code	IP 54
Safety class	I
Impact resistance class	IK03
Impact resistance	0,34999999999999999999999999999999999999
Assembly	Surface
Assembly details	Wall
Wattage	14.0 W
Lumen	750 lm
Color	anthracite
Service life	50000 h
Ambient temperature	40 °C
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	639

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	J	4	J	J	J	J	J	J	J		1			ı		1		1	ı	1	ı	J.	a,	١,	1	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	1	J.	. د	1	J	J.	ă,							



Notes			