



## PANEL 60 DALI

Indoor LED surface-mounted ceiling lights round grey 4000K

The PANEL 60 DALI ceiling light is available in several different light colours and impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V - 240V possible.

### TECHNICAL DATA

Item no.:	1003043
Primary nominal voltage	100-277V ~50/60Hz mA/V
Secondary power / secondary voltage	1000 mA/V
Height	5.5 cm
Diameter	60.0 cm
Installation diameter	20.0 cm
Installation depth	7.0 cm
Net weight	4.595 kg
Gross weight	5.317 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Ja
Dimming technology	DALI
Number of through-wires	40
Wattage	43.0 W
Lumen	3350 lm
Colour temperature	4000 Kelvin
Beam angle	110 °
Color	grey
CRI	>80



UGR ?	22.0000
Binning	6
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	257

### Notes

---

---

---

---

---