



I-PENDANT PRO DALI

Indoor LED pendant UGR<19 white 4000K

With the I-PENDANT PRO DALI, which is available with several different light colours, we are providing a modern and space-saving solution for an efficient kind of basic lighting with the additional possibility of DALI control. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting sensation. The electrical connection is made via the built-in LED power supply directly to a 100-240V mains power supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1003049 |
| Primary nominal voltage | 100-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 1000 mA/V |
| Length | 119.5 cm |
| Pendant length | 150.0 cm |
| Width | 29.5 cm |
| Height | 1.3 cm |
| Net weight | 4.4 kg |
| Gross weight | 4.708 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Ja |
| Dimming technology | DALI |
| Wattage | 43.0 W |
| Lumen | 3800 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 90 ° |
| Color | white |
| CRI | >80 |
| UGR ? | 19.0000 |



| | |
|----------------|---------|
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| BIG WHITE Page | 107 |

Notes
