


NEW TRIA 1 SET recessed fitting

single-headed LED, 3000K, square, white, 38° , 9.1W, incl. driver, clip springs

The simplicity and effectiveness of the innovative NEW TRIA 1 SET is captivating. It is available in matt black, white, or brushed aluminium, and in round or square form. Equipped with one powerful, warm white premium COB LED, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. Furthermore, it is adjustable by 38°. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Lamps included 0 Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage 350 mA/V Vertical tilting range 30 ° Length 9.0 cm Width 9.0 cm Height 3.5 cm Installation diameter 7.7 cm Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Item no.:	113911		
Secondary power / secondary voltage 350 mA/V Vertical tilting range 30 ° Length 9.0 cm Width 9.0 cm Height 3.5 cm Installation diameter 7.7 cm Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Lamps included	0		
Vertical tilting range30 °Length9.0 cmWidth9.0 cmHeight3.5 cmInstallation diameter7.7 cmInstallation depth4.0 cmNet weight0.229 kgGross weight0.283 kgIP CodeIP 20Safety classIIAssemblyRecessedAssembly detailsCeilingWattage8.0 W	Primary nominal voltage	220-240V ~50/60Hz mA/V		
Length 9.0 cm Width 9.0 cm Height 3.5 cm Installation diameter 7.7 cm Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Secondary power / secondary voltage	'secondary voltage 350 mA/V		
Width 9.0 cm Height 3.5 cm Installation diameter 7.7 cm Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Vertical tilting range	30 °		
Height 3.5 cm Installation diameter 7.7 cm Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Length	9.0 cm		
Installation diameter 7.7 cm Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Width	9.0 cm		
Installation depth 4.0 cm Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Height	3.5 cm		
Net weight 0.229 kg Gross weight 0.283 kg IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Installation diameter	7.7 cm		
Gross weight IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Installation depth	4.0 cm		
IP Code IP 20 Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Net weight	0.229 kg		
Safety class II Assembly Recessed Assembly details Ceiling Wattage 8.0 W	Gross weight	0.283 kg		
Assembly Recessed Assembly details Ceiling Wattage 8.0 W	IP Code	IP 20		
Assembly details Ceiling Wattage 8.0 W	Safety class	Ш		
Wattage 8.0 W	Assembly	Recessed		
	Assembly details	Ceiling		
700 lm	Wattage	8.0 W		
Lumen / / / / / / / / / / / / / / / / / / /	Lumen	700 lm		
Colour temperature 3000 Kelvin	Colour temperature	3000 Kelvin		
Beam angle 38 °	Beam angle	38 °		
Color white	Color	white		
CRI >80	CRI	>80		





Binning	3
LXXBXX data	70/50
Service life	40000 h
BIG WHITE Page	492

Notes			