


OUT 65

outdoor recessed ceiling light, LED, 3000K, round, white, 38° , 12W, incl. driver

The innovative OUT 65 recessed ceiling light captivates with its exceptional looks. Rated IP65 it can be used outdoors or in damp areas. It is available in black, white, silver-grey or titanium, and in round or square form. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.: 114461 Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage 500 mA/V Height 6.0 cm Diameter 8.5 cm Installation diameter 7.0 cm Installation depth 6.0 cm Net weight 0.321 kg Gross weight 0.397 kg	
Secondary power / secondary voltage 500 mA/V Height 6.0 cm Diameter 8.5 cm Installation diameter 7.0 cm Installation depth 6.0 cm Net weight 0.321 kg Gross weight 0.397 kg	
Height 6.0 cm Diameter 8.5 cm Installation diameter 7.0 cm Installation depth 6.0 cm Net weight 0.321 kg Gross weight 0.397 kg	
Diameter 8.5 cm Installation diameter 7.0 cm Installation depth 6.0 cm Net weight 0.321 kg Gross weight 0.397 kg	
Installation diameter 7.0 cm Installation depth 6.0 cm Net weight 0.321 kg Gross weight 0.397 kg	
Installation depth 6.0 cm Net weight 0.321 kg Gross weight 0.397 kg	
Net weight 0.321 kg Gross weight 0.397 kg	
Gross weight 0.397 kg	
ID 00 / ID 05	
IP Code IP 20 / IP 65	
Safety class	
Assembly Recessed	
Assembly details Ceiling	
Wattage 11.0 W	
Lumen 640 lm	
Colour temperature 3000 Kelvin	
Beam angle 38 °	
Color white	
CRI >80	
Binning 3	
LXXBXX data 70/50	
Service life 40000 h	

									4				4			4		4		4	ч	4	4	4	4	ч	4	4	4								
	٠,	ı,		ı		a,	J.	J	J	J,	J	a,	J	J	J	J	J,	a,	a,	J.	ä																
ı,	. د	ı	ı	1	J	J	1	J	1	ä	J	ä	ı	J	J	J	ä	J	ä		ä			J		4		J	J	4	J	J.	J.	1	ı	ı	J
							ы			ы		а		а	a.	а	a.	a.	a.	J.	J.	J.	а	а	л	J.	1	a.	а	а							



BIG WHITE Page	708
----------------	-----

Notes			