



COB LED MODULE

for AIXLIGHT PRO installation frame, matt white, 12°, CRI65+ $\,$

The COB LED Module was developed for use in AIXLIGHT PRO installation frames. This special product is for the lighting of meat products and is not suitable for general room lighting. The cold-white COB LED module comes in white or silver-grey and is available in various beam angles. A LED driver with a constant current of 700 mA is needed for use. Not suitable for flat installation frames.





TECHNICAL DATA

| Item no.: | 115211 | | |
|--------------------|-------------------|--|--|
| Height | 13.0 cm | | |
| Diameter | 13.5 cm | | |
| Net weight | 0.515 kg | | |
| Gross weight | 0.637 kg | | |
| IP Code | IP 20 | | |
| Assembly | Recessed | | |
| Assembly details | Ceiling with Acc. | | |
| Wattage | 26.0 W | | |
| Lumen | 1300 lm | | |
| Colour temperature | 3600 Kelvin | | |
| Beam angle | 12 ° | | |
| Color | white | | |
| CRI | >65 | | |
| | | | |



Accessories

| 1001267 | LED driver , 700mA, 40W, TRIAC dimmable |
|---------|---|
| 464032 | TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain re- lief, DALI dimmable |
| 464168 | LED DRIVER , 40W, 700mA, incl. strain relief |
| 464174 | LED DRIVER , 40W, 700mA, incl. strain relief, dimmable |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |