




SUPROS 78

recessed fitting, LED, 3000K, round, black, 60° lens, 9W

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	116310
Lamps included	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250 mA/V
Vertical tilting range	30 °
Height	7.5 cm
Diameter	11.8 cm
Installation diameter	10.8 cm
Installation depth	8.0 cm
Net weight	0.44 kg
Gross weight	0.507 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Ja
Dimming technology	trailing edge
Wattage	12.0 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black





Accessories

116302	LENS , for SUPROS 78, 20°
116304	LENS , for SUPROS 78, 40°

CRI	>80
Binning	6
LXXBXX data	70/50
Service life	25000 h
BIG WHITE Page	504

Notes
