



## MEDO 90 recessed fitting

LED, 3000K, round, black, Ø 92 cm, frosted acrylic glass, 120W

The high-quality MEDO 90 recessed ceiling light convinces with its clear form and the elegant material contrast of its aluminium and glass construction. The luminaire is available in black, white, silver grey, and wine red. Its integrated Premium LED gives pleasant lighting effects, and its built-in LED driver allows direct connection to 230V mains supply.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 135160                 |
| Lamps included                      | 0                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 2900 mA/V              |
| Height                              | 11.6 cm                |
| Diameter                            | 92.0 cm                |
| Installation diameter               | 90.5 cm                |
| Installation depth                  | 30.0 cm                |
| Net weight                          | 13.532 kg              |
| Gross weight                        | 16.311 kg              |
| IP Code                             | IP 20                  |
| Safety class                        | I                      |
| Assembly                            | Recessed               |
| Assembly details                    | Ceiling                |
| Wattage                             | 119.0 W                |
| Lumen                               | 11000 lm               |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 105 °                  |
| Color                               | black                  |
| CRI                                 | >80                    |
| UGR ?                               | 25.0000                |
| Binning                             | 6                      |



|              |         |
|--------------|---------|
| LXXBXX data  | 70/50   |
| Service life | 20000 h |

**Notes**

---

---

---

---

---