

1-PHASE RECESSED TRACK

high-voltage track, white, 2 m

Aluminium carrier track of the 240V 1-phase recessed track system. While mounting into hollow ceilings, the additional retaining bracket (143230) is required. Alternatively, there is a surface-mounted version available too.

TECHNICAL DATA

Item no.:	143221
Nominal voltage	250V ~50/60Hz V
Length	200.0 cm
Width	5.5 cm
Height	1.8 cm
Installation width	4.0 cm
Net weight	1.234 kg
Gross weight	1.789 kg
IP Code	IP 20
Safety class	I
Assembly	Recessed
Assembly details	Ceiling
Color	white
BIG WHITE Page	402

							4				4			4		4		4	4	4	4	ч	4	4	4	4	4									
	- 4	- 4		J	J.	J	J	J	J.	a,	J	J	J	J	J,	a,	a,	a,	J,																	
ı,	L	l l	J	J	1	J	J	J.	4	ä	J	J	a,	J	ä	J	ä		4			J		J.		ı	J	ı	J.	J	J.	١,	١,	1	ı	ı
					4					4		1	1	-1	1	1	а.	1	1	1	1	1	1	1	1	т.	4	1								



Accessories

1002845	Steel wire suspension for EUTRAC® , S-TRACK and 1 phase tracks, 5m, set of two
1004785	1~ track cover , white 2m

Notes			