

## L-CONNECTOR for EUT-RAC 240V 3-phase surface-mounted track

## earth electrode outside, silver-grey

Corner connector with feed capability for the 240V 3-phase surface-mounted track system. Available in various colour versions, you can also choose the ground conductor's position left or right depending on your individual installation. More detailed information can be provided on request.

## **TECHNICAL DATA**

Nominal voltage         230V ~50Hz V           Length         10.5 cm           Width         15.0 cm           Height         3.2 cm           Net weight         0.152 kg           Gross weight         0.164 kg           IP Code         IP 20           Safety class         I           Color         grey	Item no.:	145674
Width         15.0 cm           Height         3.2 cm           Net weight         0.152 kg           Gross weight         0.164 kg           IP Code         IP 20           Safety class         I           Color         grey	Nominal voltage	230V ~50Hz V
Height         3.2 cm           Net weight         0.152 kg           Gross weight         0.164 kg           IP Code         IP 20           Safety class         I           Color         grey	Length	10.5 cm
Net weight         0.152 kg           Gross weight         0.164 kg           IP Code         IP 20           Safety class         I           Color         grey	Width	15.0 cm
Gross weight         0.164 kg           IP Code         IP 20           Safety class         I           Color         grey	Height	3.2 cm
IP Code IP 20 Safety class I Color grey	Net weight	0.152 kg
Safety class     Color   grey	Gross weight	0.164 kg
Color grey	IP Code	IP 20
	Safety class	I
	Color	grey
BIG WHITE Page 370	BIG WHITE Page	370

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J.	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	LL	1 1	ı	J	J	J	J	J.	J	ä	J	J	J	J	J	J	J		4			ı		1		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					á			á		ä		J	ä	J	ä	J	J	J	J.	J	J.	a.	J.	J	J	J	J.	ă,								


