

PENDANT SUSPENSION for EUTRAC 240V 3-phase surface-mounted track

rigid, white, 60 cm, M13 thread

Rigid pendant suspension for the 240V 3-circuit surface-mounted track system. The suspension comes in several colours and lengths and can be used in combination with the joint connector or pendant clip anywhere on the track. It is possible to shorten it on-site. Please note that the white tone will be changing from RAL 9010 to RAL 9016 (traffic white) on 1st April 2018. More information can be found under Product Information in the ?Service? / Downloads area.

TECHNICAL DATA

| Item no.: | 145721 |
|------------------|----------|
| Length | 60.0 cm |
| Height | 63.5 cm |
| Diameter | 7.0 cm |
| Net weight | 0.272 kg |
| Gross weight | 0.289 kg |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Color | white |

| | | | | | | | 4 | | | | 4 | | | 4 | | ч | | ч | ч | ч | ч | ч | J | 4 | 4 | 4 | 4 | | | | | | | | |
|----|-----|-----|---|---|----|----|----|----|---|---|---|---|---|---|---|---|---|---|----|---|----|----|----|-----|---|---|----|----|---|----|----|----|---|---|---|
| | 4 | - 4 | | ı | a, | J, | J. | J | 4 | a | J | J | J | J | ä | a | ä | ä | J. | | | | | | | | | | | | | | | | |
| ١. | ı . | LL | 1 | 1 | ı | ı | J | J. | 4 | 4 | J | J | J | J | J | J | J | | 1 | | | ı | | 1 | | 1 | ı | 1 | ı | J. | a, | ١, | 1 | 1 | 1 |
| | | | | | ı | | | á | | ā | | J | ä | J | ä | ä | J | J | J. | J | J. | J. | J. | . د | 1 | J | J. | ă, | | | | | | | |



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |