

KALU wall and ceiling light

single-headed, QR111, round, matt black, max. 50 W

The puristic design of the wall and ceiling light KALU is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with QRB halogen or suitable LED lamps. Equipped with soft-start function, the incorporated electronic transformer protects the bulbs from potential damage from over-voltage. The light can be dimmed which offers even more installation possibilities. Available in matt white, matt black or brushed aluminium colour, KALU is supplied ready for direct connection to 230V mains supply.

TECHNICAL DATA

| Item no.: | 147250 | | |
|-------------------------------------|-----------------|--|--|
| Socket | G53 | | |
| Lamp | QR111 | | |
| Number of sockets | 1 | | |
| Lamps included | 0 | | |
| Primary nominal voltage | 230V ~50Hz mA/V | | |
| Secondary power / secondary voltage | 12 mA/V | | |
| Tilt range | 90 ° | | |
| Horizontal rotation range | 350 ° | | |
| Width | 15.0 cm | | |
| Height | 19.0 cm | | |
| Depth | 9.0 cm | | |
| Net weight | 0.569 kg | | |
| Gross weight | 0.742 kg | | |
| IP Code | IP 20 | | |
| Safety class | I | | |
| Assembly | Surface | | |
| Assembly details | Ceiling,Wall | | |
| Wattage | 50.0 W | | |
| Color | black | | |
| | · | | |





Recommended lamp

| 551412 | LED QRB111 , lamp, CREE XB-D LED, grey, 19,5W, 140°, 2700K |
|--------|--|
| 560231 | PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable |
| 560233 | PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |