

RETROSIX

wall and ceiling light, triple-headed, QR111, black acrylic glass, max. 150 $\ensuremath{\mathrm{W}}$

With our 230V wall and ceiling light RETROSIX we offer a nostalgic design which, by modern interpretation, provides illumination with a distinctive character. It is available with an either clear or blackened glass cover. Prepared for the use of low-voltage QRB or appropriate LED retrofit lamps, RETROSIX is ready for direct connection to 230V mains supply via the incorporated, electronic transformer.

TECHNICAL DATA

| Item no.: | 147593 |
|-------------------------------------|------------------------|
| Socket | G53 |
| Lamp | QR111 |
| Number of sockets | 3 |
| Lamps included | 0 |
| Primary nominal voltage | 230-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 12 mA/V |
| Tilt range | 60 ° |
| Horizontal rotation range | 360 ° |
| Length | 56.8 cm |
| Width | 17.5 cm |
| Height | 12.8 cm |
| Net weight | 3.025 kg |
| Gross weight | 3.339 kg |
| IP Code | IP 20 |
| Safety class | 1 |
| Assembly | Surface |
| Wattage | 50.0 W |
| Color | black |
| | |

| | | | | | | | 4 | | | | 4 | | | 4 | | ч | | ч | ч | ч | ч | ч | J | 4 | 4 | 4 | 4 | | | | | | | | |
|----|-----|-----|---|---|----|----|----|----|---|---|---|---|---|---|---|---|---|---|----|---|----|----|----|-----|---|---|----|----|---|----|----|----|---|---|---|
| | 4 | - 4 | | ı | a, | J, | J. | J | 4 | a | J | J | J | J | ä | a | ä | ä | J. | | | | | | | | | | | | | | | | |
| ١. | ı . | LL | 1 | 1 | ı | ı | J | J. | J | 4 | J | J | J | J | J | J | J | | 4 | | | ı | | 1 | | 1 | ı | 1 | ı | J. | a, | ١, | 1 | 1 | 1 |
| | | | | | ı | | | á | | ā | | J | ä | J | ä | ä | J | J | J. | J | J. | J. | J. | . د | 1 | J | J. | ă, | | | | | | | |



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |