

RETO

ceiling light, LED, 2700K, grey/white, 4.4W

The RETO ceiling light is made from aluminium and glass elements and is fitted with two further frosted glass cylinders. Both of the integrated 4.4 Watt LEDs offer a beautiful lighting effect. The special characteristic of the luminaire is the high colour rendering index of 90. With its strong design, the RETO ceiling light can be directly connected to the 230V mains supply as it has a LED driver built-in. There are other variants available in the series too.

TECHNICAL DATA

Lamps included0Number of different light outlets1Primary nominal voltage220-240V ~50/60Hz mA/VSecondary power / secondary voltage365 mA/VHeight18.5 cmDiameter12.5 cmNet weight1.055 kgGross weight1.259 kgIP CodeIP 20Safety classIAssemblySurfaceAssembly detailsCeilingWattage12.0 WLumen550 lmColour temperature2700 KelvinColorgrey	Item no.:	150654
Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage 365 mA/V Height 18.5 cm Diameter 12.5 cm Net weight 1.055 kg Gross weight 1.259 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Lamps included	0
Secondary power / secondary voltage 365 mA/V Height 18.5 cm Diameter 12.5 cm Net weight 1.055 kg Gross weight 1.259 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 Im Colour temperature 2700 Kelvin Color grey	Number of different light outlets	1
Height 18.5 cm Diameter 12.5 cm Net weight 1.055 kg Gross weight 1.259 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Primary nominal voltage	220-240V ~50/60Hz mA/V
Diameter 12.5 cm Net weight 1.055 kg Gross weight 1.259 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Secondary power / secondary voltage	365 mA/V
Net weight 1.055 kg Gross weight 1.259 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Height	18.5 cm
Gross weight 1.259 kg IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Diameter	12.5 cm
IP Code IP 20 Safety class I Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 Im Colour temperature 2700 Kelvin Color grey	Net weight	1.055 kg
Safety class Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 Im Colour temperature 2700 Kelvin Color grey	Gross weight	1.259 kg
Assembly Surface Assembly details Ceiling Wattage 12.0 W Lumen 550 Im Colour temperature 2700 Kelvin Color grey	IP Code	IP 20
Assembly details Ceiling Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Safety class	I
Wattage 12.0 W Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Assembly	Surface
Lumen 550 lm Colour temperature 2700 Kelvin Color grey	Assembly details	Ceiling
Color temperature 2700 Kelvin grey	Wattage	12.0 W
Color grey	Lumen	550 lm
	Colour temperature	2700 Kelvin
	Color	grey
CHI >90	CRI	>90
LXXBXX data 70/50	LXXBXX data	70/50
Service life 30000 h	Service life	30000 h

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	4	4	J	J	J	J	J	J	J		1			ı		1		1	ı	1	ı	J.	a,	١,	1	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	J.	J.	. د	1	J	J.	ă,							



Notes			