




DOWNUNDER PUR 80

recessed fitting, LED, 3000K, square, white, L/W/H 8/3.2/8 cm, incl. leaf springs

Aluminium recessed wall light of our DOWNUNDER 80 series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 80 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 350mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.:	151950
Lamps included	0
Secondary power / secondary voltage	350 mA/V
Width	8.0 cm
Height	8.0 cm
Depth	3.2 cm
Installation length	7.0 cm
Installation width	6.5 cm
Installation depth	3.5 cm
Net weight	0.129 kg
Gross weight	0.175 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	3.6 W
Lumen	180 lm
Colour temperature	3000 Kelvin
Color	white
CRI	>80
LXXBXX data	70/50
Service life	30000 h



Accessories

151960	FLUSH-MOUNTED FRAME , for DOWNUNDER PUR 80, L/H 14/14 cm
464109	LED DRIVER , 9W, 350mA
464140	LED DRIVER , 10W, 350mA, incl. strain relief, dimmable

Notes