




DOWNUNDER PUR 120

recessed fitting, LED, 3000K, square, white, L/W/H
8/3.2/12 cm, incl. leaf springs

Aluminium recessed wall light of our DOWNUNDER 120 series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 120 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 350mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	151951
Lamps included	0
Secondary power / secondary voltage	350 mA/V
Width	8.0 cm
Height	12.0 cm
Depth	3.2 cm
Installation length	11.0 cm
Installation width	6.5 cm
Installation depth	3.5 cm
Net weight	0.168 kg
Gross weight	0.222 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	3.6 W
Lumen	160 lm
Colour temperature	3000 Kelvin
Color	white
CRI	>80
LXXBXX data	70/50
Service life	30000 h

Accessories

1002803	LED driver , 9.1 - 15W 350mA, dimmable
151961	FLUSH-MOUNTED FRAME , for DOWNUNDER PUR 120, L/H 14/18 cm
464109	LED DRIVER , 9W, 350mA

Notes
