



SUPROS 78

spot for 240V 3-phase tracks, LED, 3000K, round, black, 60° lens, 9W, incl. 3-phase adapter

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	152660
Lamps included	1
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250 mA/V
Vertical tilting range	190 °
Horizontal rotation range	350 °
Length	23.4 cm
Height	19.2 cm
Diameter	7.8 cm
Net weight	0.922 kg
Gross weight	1.076 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Track Ceiling
Dimmable	Ja
Dimming technology	trailing edge
Wattage	12.0 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	60 °

Accessories

1000677	ANTI-GLARE CAPS for SUPROS 78 , black
1000678	ANTI-GLARE CAPS , for SUPROS 78, white
116302	LENS , for SUPROS 78, 20°
116304	LENS , for SUPROS 78, 40°

Color	black
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	25000 h
BIG WHITE Page	354

Notes
