а. л J Л а. 111 ы . л Л л л






SUPROS

spot for 240V 3-phase track, LED, 3000K, white, 60° reflector, 33.5W, incl. 3-phase adapter

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

Item no.:	152801	
Lamps included	0	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	950 mA/V	
Vertical tilting range	190 °	
Horizontal rotation range	350 °	
Length 24.5 cm		
Height	21.5 cm	
Diameter	neter 12.7 cm	
Net weight	1.611 kg	
Gross weight	1.805 kg	
IP Code	IP 20	
Safety class	1	
Assembly	Surface	
Assembly details	Ceiling,Track Ceiling	
Wattage	36.0 W	
Lumen	3100 lm	
Colour temperature	3000 Kelvin	
Beam angle	60 °	
Color	white	
CRI	>80	
Binning	3	



		LXXBXX data	70/50
Accessories		Service life	50000 h
		BIG WHITE Page	355
1000679	ANTI-GLARE CAPS , for SUPROS, black		
1000680	ANTI-GLARE CAPS , for SUPROS, white		
114102	REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring		
114104	REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring		

Notes