

TEC 1 spot for 240V 3-phase track

single-headed, QR111, silver-grey, max. 50W, incl. 3-phase adapter

Adjustable low-voltage spot TEC 1 with suitable adapter for the 240V 3-phase track system. The lamp head is multi-directional at the lamps housing that contains the electronic transformer.

TECHNICAL DATA

| Item no.: | 153002 | | |
|-------------------------------------|-----------------------|--|--|
| Socket | G53 | | |
| Lamp | QR111 | | |
| Number of sockets | 1 | | |
| Lamps included | 0 | | |
| Primary nominal voltage | 230V ~50Hz mA/V | | |
| Secondary power / secondary voltage | 12 mA/V | | |
| Length | 14.0 cm | | |
| Width | 18.0 cm | | |
| Height | 19.5 cm | | |
| Net weight | 0.627 kg | | |
| Gross weight | 0.867 kg | | |
| IP Code | IP 20 | | |
| Safety class | I | | |
| Assembly | Surface | | |
| Assembly details | Ceiling,Track Ceiling | | |
| Wattage | 50.0 W | | |
| Color | grey | | |
| | | | |





Recommended lamp

| 545522 HALOSPOT111 ECO , low-pressure halogen, EnergySaver, 12V, 2900K, 35W, 24° | 545522 |
|--|--------|
|--|--------|

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |