



KARDATRACK

pendant for 3-phase 240V track, four-headed,
QR-LP111, silver-grey, max. 200W, incl. 3-phase ad-
apter

Four-headed low-voltage spot KARDATRACK with suitable adapter for the 3-phase 240V track system. By the nature of their mountings, the four bulbs within the frame can be independently tilted and turned in a multi-directional manner. The electronic transformer, which is dimmable, is located in the middle part of the frame. With the G53 socket fitted, the luminaire is suitable for halogen and LED lamps with a diameter of up to 11.1 cm.

TECHNICAL DATA

Item no.:	154512
Socket	G53
Lamp	QR111
Number of sockets	4
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Secondary power / secondary voltage	12 mA/V
Length	86.5 cm
Width	19.0 cm
Height	18.0 cm
Net weight	2.653 kg
Gross weight	3.28 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Track Ceiling, Track Wall, Wall
Wattage	50.0 W
Color	grey

Recommended lamp

545522	HALOSPOT111 ECO , low-pressure halogen, EnergySaver, 12V, 2900K, 35W, 24°
--------	---

Notes
