



## Q-LINE

pendant, single-headed, T16, natural aluminium/anthracite, energy saving lamp, max. 35W, incl. electronic ballast

The Q-LINE pendant is available with a white or aluminium-painted lamp housing and fitted with matching end caps in anthracite or chrome. A diffuser made of acrylic glass found underneath provides glare-free lighting properties. Designed to take a T5 fluorescent tube with 35W output, the pre-installed ballast allows the luminaire to be directly connected to the 230V mains supply. The optionally available long connectors mean that several Q-LINE pendants can be connected together in just a few steps.

## TECHNICAL DATA

Item no.:	155012
Socket	G5
Lamp	T16
Number of sockets	1
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Length	151.0 cm
Pendant length	200.0 cm
Width	5.7 cm
Height	9.8 cm
Net weight	3.059 kg
Gross weight	3.875 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Number of through-wires	15
Wattage	38.0 W
Color	aluminium

## Recommended lamp

548035	T5 , fluorescent tube 35W, 3000K
--------	----------------------------------

## Accessories

155051	LONGITUDINAL CONNECTOR for Q-LINE WALL , white/chrome
155052	LONGITUDINAL CONNECTOR for Q-LINE WALL , natural aluminium
155062	CORNER CONNECTOR , for Q-LINE WALL

## Notes

---

---

---

---

---