





## Q-LINE DALI

pendant, single-headed, LED, 3000K, black, dimmable, 2x18,2W and 1x7,5W

The Q-LINE DALI wall light is available with a choice of a white, back, or silver-grey luminaire housing. A diffuser made of acrylic glass found underneath provides glare-free lighting properties. The integrated warm-white LEDs give an output of 3200 lm. Thanks to the DALI dimmable LED driver, the luminaire can be directly connected to the 230V mains supply.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 155130                 |
| Lamps included                      | 0                      |
| Number of different light outlets   | 1                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 100400 mA/V            |
| Length                              | 142.0 cm               |
| Pendant length                      | 200.0 cm               |
| Width                               | 6.0 cm                 |
| Height                              | 6.0 cm                 |
| Net weight                          | 3.389 kg               |
| Gross weight                        | 3.938 kg               |
| IP Code                             | IP 20                  |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling                |
| Dimmable                            | Ja                     |
| Dimming technology                  | DALI                   |
| Wattage                             | 47.0 W                 |
| Lumen                               | 3200 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 120 °                  |
| Color                               | black                  |



|                |         |
|----------------|---------|
| CRI            | >80     |
| Binning        | 4       |
| Binning 2      | 4       |
| LXXBXX data    | 70/50   |
| Service life   | 30000 h |
| Service life 2 | 30000 h |

**Notes**

---

---

---

---

---