





LED PANEL

recessed and surface-mounted ceiling light, 2700K, square, matt white, L/W/H 59.5/59.5/1.5 cm, 39.5W

The LED PANEL comes in several colours of light, which we offer in a modern, space-saving solution for an efficient type of base lighting. With a luminous flux of approx. 3200 lumens, you achieve a pleasant, uniform and glare-free illumination. The electrical connection is made directly to the 230V mains supply thanks to the built-in LED power supply.



TECHNICAL DATA

Item no.:	158602
Lamps included	0
Primary nominal voltage	100-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1340 mA/V
Length	59.5 cm
Width	59.5 cm
Height	1.5 cm
Installation length	60.0 cm
Installation width	60.0 cm
Net weight	4.004 kg
Gross weight	4.945 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Wattage	40.0 W
Lumen	3250 lm
Colour temperature	2700 Kelvin
Beam angle	110 °
Color	white
CRI	>80
UGR ?	22.0000

Accessories

158762	INSTALLATION FRAME , for LED-PANEL, I-VIDUAL and I-VIDUAL PANEL, matt white, L/W/H 60/60/5.5 cm
470505	EP1 DIMMER , 1-10V, max. 10W

Binning	6
LXXBXX data	70/50
Service life	30000 h

Notes
