





LED PANEL

recessed and surface-mounted ceiling light, 3000K, square, matt white, L/W/H 59.5/59.5/1.5 cm, 39.5W

The LED PANEL comes in several colours of light, which we offer in a modern, space-saving solution for an efficient type of base lighting. With a luminous flux of approx. 3200 lumens, you achieve a pleasant, uniform and glare-free illumination. The electrical connection is made directly to the 230V mains supply thanks to the built-in LED power supply.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 158603 |
| Lamps included | 0 |
| Primary nominal voltage | 100-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 1340 mA/V |
| Length | 59.5 cm |
| Width | 59.5 cm |
| Height | 1.5 cm |
| Installation length | 60.0 cm |
| Installation width | 60.0 cm |
| Net weight | 4.049 kg |
| Gross weight | 5.048 kg |
| IP Code | IP 20 |
| Safety class | II |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 40.0 W |
| Lumen | 3250 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 110 ° |
| Color | white |
| CRI | >80 |
| UGR ? | 22.0000 |

Accessories

| | |
|--------|---|
| 158762 | INSTALLATION FRAME , for LED-PANEL, I-VIDUAL and I-VIDUAL PANEL, matt white, L/W/H 60/60/5.5 cm |
| 470505 | EP1 DIMMER , 1-10V, max. 10W |

| | |
|--------------|---------|
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |

Notes
