


LED PANEL 360

recessed fitting, 3000K, round, white, without a driver, 40W

The LED PANEL 360 comes in a number of different light colours and offers a modern and space-saving solution for efficient base lighting. Due to the variable constant current power supply of 1000mA to 1050mA, various standard or dimmable drivers can be used. With this product you reach a pleasant, homogeneous and glare-free lighting feeling.



TECHNICAL DATA

Item no.:	158663		
Lamps included	0		
Secondary power / secondary voltage	10001050 mA/V		
Height	4.0 cm		
Diameter	60.0 cm		
Installation diameter	59.0 cm		
Installation depth	6.0 cm		
Net weight	2.493 kg		
Gross weight	3.265 kg		
IP Code	IP 20		
Safety class	III		
Assembly	Recessed		
Assembly details	Ceiling		
Wattage	34.0 W		
Lumen	2630 lm		
Colour temperature	3000 Kelvin		
Beam angle	120°		
Color	white		
CRI	>80		
UGR ?	22.0000		
Binning	6		
LXXBXX data	70/50		
	'		



Accessories

464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Service life	30000 h
BIG WHITE Page	522

Notes		