


I-VIDUAL

LED panel for grid ceilings, 4000K, silver-grey, L/W
59.5/59.5 cm

The 60 x 60 cm grid I-VIDUAL, available with a number of different colours of light, offers a modern and space saving solution for efficient basic lighting needs. Due to the variable constant current power supply of 1000mA to 1050mA, various standard or dimmable drivers can be used. With this product you reach a pleasant, homogeneous and glare-free lighting feeling. Ideal as a replacement for old tube systems.



TECHNICAL DATA

| | |
|-------------------------------------|---------------|
| Item no.: | 158744 |
| Lamps included | 0 |
| Secondary power / secondary voltage | 10001050 mA/V |
| Length | 59.5 cm |
| Width | 59.5 cm |
| Height | 1.3 cm |
| Installation depth | 5.0 cm |
| Net weight | 3.933 kg |
| Gross weight | 4.7 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 35.0 W |
| Lumen | 3650 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 110 ° |
| Color | grey |
| CRI | >80 |
| UGR ? | 22.0000 |
| Binning | 6 |
| LXXBXX data | 70/50 |

Service life

30000 h

Accessories

| | |
|--------|---------------------------------------------------------------------------------------------------|
| 158762 | INSTALLATION FRAME , for LED-PANEL, I-VIDUAL and I-VIDUAL PANEL, matt white, L/W/H 60/60/5.5 cm |
| 158764 | INSTALLATION FRAME , for I-VIDUAL LED panel, silver-grey, L/W 60.5/60.5 cm |
| 158791 | CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white |
| 158799 | SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension |
| 464032 | TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable |
| 464170 | LED DRIVER , 40W, 1000mA, incl. strain relief |
| 464176 | LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable |
| 464804 | LED DRIVER , 40W, 1050mA, triac dimmable |

Notes
