


I-VIDUAL

recessed fitting, LED, 4000K, silver, for grid ceilings,
L/W/H 59.5/59.5/1.3 cm, 35W

The 60 x 60 cm grid I-VIDUAL, available with a number of different colours of light, offers a modern and space saving solution for efficient basic lighting needs. Due to the variable constant current power supply of 1000mA to 1050mA, various standard or dimmable drivers can be used. With this product you reach a pleasant, homogeneous and glare-free lighting feeling. An aperture angle of under 19 is achieved here.



TECHNICAL DATA

Item no.:	158824
Lamps included	0
Secondary power / secondary voltage	10001050 mA/V
Length	59.5 cm
Width	59.5 cm
Height	1.3 cm
Installation depth	5.0 cm
Net weight	4.372 kg
Gross weight	4.948 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	35.0 W
Lumen	3900 lm
Colour temperature	4000 Kelvin
Beam angle	90 °
Color	grey
CRI	>80
UGR ?	22.0000
Binning	6
LXXBXX data	70/50

Service life

30000 h

Accessories

158762	INSTALLATION FRAME , for LED-PANEL, I-VIDUAL and I-VIDUAL PANEL, matt white, L/W/H 60/60/5.5 cm
158764	INSTALLATION FRAME , for I-VIDUAL LED panel, silver-grey, L/W 60.5/60.5 cm
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Notes
