





SENSER 18

recessed fitting, LED, 3000K, round, white, 10W

The SENSER 18 recessed light made from aluminium is available in matt white or silver-grey finish, as well as with round or square shade. The 120° beam angle of the fixed, Premium LED module provides a broad and uniform base illumination. A suitable constant current driver providing 350mA is required to operate the recessed fitting.





TECHNICAL DATA

Lamps included Secondary power / secondary voltage Height 3.0 cm Diameter 18.0 cm Installation diameter 17.2 cm Installation depth 4.0 cm Net weight 0.403 kg Gross weight IP Code IP 20 Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen Colour temperature 3000 Kelvin Beam angle 120 ° Color white CRI	Item no.:	162713
Secondary power / secondary voltage350 mA/VHeight3.0 cmDiameter18.0 cmInstallation diameter17.2 cmInstallation depth4.0 cmNet weight0.403 kgGross weightIP 20Safety classIIIAssemblyRecessedAssembly detailsCeilingWattage10.0 WLumen560 lmColour temperature3000 KelvinBeam angle120 °Colorwhite		
Height 3.0 cm Diameter 18.0 cm Installation diameter 17.2 cm Installation depth 4.0 cm Net weight 0.403 kg Gross weight 0.554 kg IP Code IP 20 Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen 560 lm Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Lamps included	0
Diameter18.0 cmInstallation diameter17.2 cmInstallation depth4.0 cmNet weight0.403 kgGross weight0.554 kgIP CodeIP 20Safety classIIIAssemblyRecessedAssembly detailsCeilingWattage10.0 WLumen560 lmColour temperature3000 KelvinBeam angle120 °Colorwhite	Secondary power / secondary voltage	350 mA/V
Installation diameter 17.2 cm Installation depth 4.0 cm Net weight 0.403 kg Gross weight 0.554 kg IP Code IP 20 Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen 560 lm Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Height	3.0 cm
Installation depth 4.0 cm Net weight 0.403 kg Gross weight 0.554 kg IP Code IP 20 Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen 560 lm Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Diameter	18.0 cm
Net weight 0.403 kg Gross weight 0.554 kg IP Code IP 20 Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen 560 lm Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Installation diameter	17.2 cm
Gross weight IP Code IP 20 Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Installation depth	4.0 cm
IP Code Safety class III Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Net weight	0.403 kg
Safety class Assembly Recessed Ceiling Wattage 10.0 W Lumen 560 Im Colour temperature 3000 Kelvin Beam angle 120 ° White	Gross weight	0.554 kg
Assembly Recessed Assembly details Ceiling Wattage 10.0 W Lumen 560 Im Colour temperature 3000 Kelvin Beam angle 120 ° Color white	IP Code	IP 20
Assembly details Ceiling Wattage 10.0 W Lumen 560 lm Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Safety class	III
Wattage10.0 WLumen560 lmColour temperature3000 KelvinBeam angle120 °Colorwhite	Assembly	Recessed
Lumen 560 lm Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Assembly details	Ceiling
Colour temperature 3000 Kelvin Beam angle 120 ° Color white	Wattage	10.0 W
Beam angle 120 ° Color white	Lumen	560 lm
Color white	Colour temperature	3000 Kelvin
	Beam angle	120 °
CRI >80	Color	white
	CRI	>80
Binning 6	Binning	6
LXXBXX data 70/50	LXXBXX data	70/50
Service life 30000 h	Service life	30000 h

							4				4			4		4		4	4	4	4	ч	4	4	4	4	4									
	- 4	- 4		J	J.	J	J	J	J.	a,	J	J	J	J	J,	a,	a,	a,	J,																	
ı,	L	l l	J	J	1	J	J	J.	4	ä	J	J	a,	J	ä	J	ä		4			J		J.		ı	J	ı	J.	J	J.	١,	١,	1	ı	ı
					4					4		1	1	-1	1	1	а.	1	1	1	1	1	1	1	1	т.	4	1								



Accessories

1002803	LED driver , 9.1 - 15W 350mA, dim- mable

Notes		