





SENSER 24

recessed fitting, LED, 3000K, round, white, 14W

The SENSER 24 recessed light made from aluminium is available in matt white or silver-grey finish, as well as with round or square shade. The 120° beam angle of the fixed, Premium LED module provides a broad and uniform base illumination. A suitable constant current driver providing 350mA is required to operate the recessed fitting.





TECHNICAL DATA

| Item no.: | 162723 |
|-------------------------------------|-------------|
| Lamps included | 0 |
| Secondary power / secondary voltage | 350 mA/V |
| Height | 3.0 cm |
| Diameter | 24.0 cm |
| Installation diameter | 23.0 cm |
| Installation depth | 4.0 cm |
| Net weight | 0.646 kg |
| Gross weight | 0.875 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 14.0 W |
| Lumen | 970 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120 ° |
| Color | white |
| CRI | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |

| | | | | | | | 4 | | | | 4 | | | 4 | | 4 | | 4 | 4 | 4 | 4 | ч | 4 | 4 | 4 | 4 | 4 | | | | | | | | | |
|----|-----|-----|---|----|----|---|---|----|----|----|---|---|----|----|----|----|----|----|----|---|---|---|---|----|---|----|---|---|----|---|----|----|----|---|---|---|
| | - 4 | - 4 | | J. | J. | J | J | J | J. | a, | J | J | J | J | J, | a, | a, | a, | J, | | | | | | | | | | | | | | | | | |
| ı, | L | l l | J | J | 1 | J | J | J. | 4 | ä | J | J | a, | J | ä | J | ä | | 4 | | | J | | J. | | ı | J | ı | J. | J | J. | ١, | ١, | 1 | ı | ı |
| | | | | | 4 | | | | | 4 | | 1 | 1 | -1 | 1 | 1 | а. | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | т. | 4 | 1 | | | | | | | | |



Accessories

| 1002803 | LED driver , 9.1 - 15W 350mA, dim- mable |
|---------|---|
| | |

| Notes | | |
|-------|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |