

PENTULI

pendant, LED, 3000K, black, Ø 24 cm, black canopy, 31W

The PENTULI LED pendant features classic design, is available in both black and white, and possesses a high output LED module with a beam angle of 30°. The luminaire comes with a 1.5 metre long connection lead, and thanks to a built-in LED driver, is ready for direct connection to 230V mains supply.

TECHNICAL DATA

| Lamps included (| 0 |
|-------------------------------------|------------------------|
| | |
| Primary nominal voltage | 120-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 900 mA/V |
| Pendant length | 150.0 cm |
| Height 2 | 27.5 cm |
| Diameter | 24.5 cm |
| Net weight | 1.793 kg |
| Gross weight 2 | 2.217 kg |
| IP Code | IP 20 |
| Safety class | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Wattage | 36.0 W |
| Lumen | 2550 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 30 ° |
| Color | black |
| CRI : | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |

| | | | | | | | 4 | | | | 4 | | | 4 | | ч | | ч | ч | ч | ч | ч | J | 4 | 4 | 4 | 4 | | | | | | | | |
|----|-----|-----|---|---|----|----|----|----|---|---|---|---|---|---|---|---|---|---|----|---|----|----|----|-----|---|---|----|----|---|----|----|----|---|---|---|
| | 4 | - 4 | | ı | a, | J, | J. | J | 4 | a | J | J | J | J | ä | a | ä | ä | J. | | | | | | | | | | | | | | | | |
| ١. | ı . | LL | 1 | 1 | ı | ı | J | J. | J | 4 | J | J | J | J | J | J | J | | 1 | | | ı | | 1 | | 1 | ı | 1 | ı | J. | a, | ١, | 1 | 1 | 1 |
| | | | | | ı | | | á | | ā | | J | ä | J | ä | ä | J | J | J. | J | J. | J. | J. | . د | 1 | J | J. | ă, | | | | | | | |



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |