


## S-TRACK 3-phase surface-mounted track

## 240V track, silver-grey, 1 m

Aluminium bearing track of the 240V 3-phase surface-mounted track system. Installation can be done through the existing holes in the profile directly onto the wall or the ceiling. The surface-mounted version of this system is available in several colours and lengths. Alternatively, there is a recessed version available too.



## **TECHNICAL DATA**

Item no.:	175014
Nominal voltage	220-250V ~50Hz V
Length	99.5 cm
Width	3.6 cm
Height	3.6 cm
Net weight	0.908 kg
Gross weight	1.141 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
BIG WHITE Page	365

							4				4			4		4		4	4	4	ч	ч	4	4	4	ч	4									
	- 4	- 4		ä	J.	J	J	J	J	J.	J	J	J	J	J,	a,	ä	a,	a,																	
ı,		ר ר	J	J	1	J	J	J.	J	1	J	J	J	J	ä	J	ä		a,			J.		J		J	J	4	J	J	a,	. د	1 .	L	4	
					ы			ы		а		а	а	а	л	л	a.	J.	J.	а.	a.	J.	a.	ı	ı	J.	а	а								



## Accessories

1002845	Steel wire suspension for EUTRAC® , S-TRACK and 1 phase tracks, 5m, set of two
---------	--

Notes			